




















TECHNICAL CHARACTERISTICS

CARACTERÍSTICAS TÉCNICAS

	ISO 13006 UNE-EN 14411	Bla (Porcelain)	Billi (White Body)
 Longitud y anchura <i>Length and width</i>	EN ISO 10545-2	± 0,6 % ± 2,0 mm	± 0,5 % ± 2,0 mm
 Espesor <i>Thickness</i>	EN ISO 10545-2	± 5 % ± 0,5 mm	± 10 % ± 0,5 mm
 Rectitud de lados <i>Straightness of sides</i>	EN ISO 10545-2	± 0,5 % ± 1,5 mm	± 0,5 %
 Ortogonalidad <i>Rectangularity</i>	EN ISO 10545-2	± 0,5 % ± 2,0 mm	± 0,3 % ± 1,5 mm
 Planitud de superficie <i>Surface flatness</i>	EN ISO 10545-2	± 0,5 % ± 2,0 mm	+ 0,5 % ; - 0,3 % + 2 mm ; - 1,5 mm
 Absorción de agua <i>Water absorption</i>	EN ISO 10545-3	E ≤ 0,5 % Max. Individual 0,6%	E > 10 %
 Fuerza de rotura (N) * <i>Breaking strength *</i>	EN ISO 10545-4	E > 7,5 mm > 1300 N E < 7,5 mm > 700 N	E > 7,5 mm > 600 N E < 7,5 mm > 200 N
 Resistencia a la flexión (N/mm ²) <i>Modulus of rupture</i>	EN ISO 10545-4	> 35 N/mm ² Min. Individual 35 N/mm ²	E > 7,5 > 12 N/mm ² E < 7,5 > 15 N/mm ²
 Resistencia a la abrasión profunda (Solo UGL) <i>Surface deep abrasion resistance (Only UGL)</i>	EN ISO 10545-6	Min. 175 mm ³	No aplica Not apply
 Resistencia a la abrasión superficial (Solo GL) <i>Surface abrasion resistance (Only GL)</i>	EN ISO 10545-7	Valor declarado Declared value	No aplica Not apply
 Coeficiente de dilatación térmica lineal (1/k) <i>Coefficient of linear thermal expansion</i>	EN ISO 10545-8	Valor declarado Declared value	Valor declarado Declared value
 Resistencia al choque térmico <i>Thermal shock resistance</i>	EN ISO 10545-9	Resiste Resist	Resiste Resist
 Resistencia al cuarteo <i>Crazing resistance</i>	EN ISO 10545-11	Resiste Resist	Resiste Resist
 Resistencia a la helada <i>Frost resistance</i>	EN ISO 10545-12	Resiste Resist	No resiste Not resist
 Deslizamiento <i>Coefficient of friction</i>	UNE ENV 41901 DIN 51130 DIN 51097 ANSI A137.1	Valor declarado Declared value	No aplica Not apply
 Resistencia a productos de limpieza y aditivos para piscina <i>Resistance to household chemicals and swimming pool salts</i>	EN ISO 10545-4	Min GB	Min GB
 Resistencia a bajas concentraciones <i>Resistance to low concentrations</i>	EN ISO 10545-13	GLA / GLB (Pulido) GLA / GLB (Polished)	GLA
 Resistencia a altas concentraciones <i>Resistance to high concentrations</i>	EN ISO 10545-13	GHA / GHB (Pulido) GHA / GHB (Polished)	GHA
 Resistencia a las manchas <i>Resistance to stains</i>	EN ISO 10545-14	> 3	> 3

*Las características indicadas son generales por grupo de absorción, para características concretas de modelo y color solicitar la ficha técnica correspondiente.

*The characteristics indicated are general for each absorption group, for specific characteristics of the model and color, please request the corresponding technical data sheet.