



DATA SHEET

Collection

ANTIC COLLECTION

Manufacture process	Nominal size (mm)	Group
Red body, double firing	75X150X9	BIII
TEST	RESULT	TESTING STANDARD
Piece finishing	GLOSS	-
Surface	RELIEF	-
Water absorption	E>10%	UNE-EN ISO 10545-3
Breaking strength N/mm²	E>12 N/mm2	UNE-EN ISO 10545-4
Thermal shock resistance	Resist	UNE-EN ISO 10545-9
Crazing resistance	Resist	UNE-EN ISO 10545-11
Chemical resistance	Туре А	UNE-EN ISO 10545-13
Resistance to stains	Class 5	UNE-EN ISO 10545-14
Tone Variation	UNIFORM V1	-

APPLICATIONS AND SAFETY INFORMATION

Material for walls

Joint: 3 mm joint with any wall tile grout

Adhesives: any wall and floor tiles adhesives type C1

 $\star \rm VERDE$ VIC / $\star \rm METAL:$ Glaze with high reaction to acids. Clean only with water and neutral soap

CEVICA, SL. - Pol. Industrial Pullman, Calle Hungria nº18 , 12006 Castellon de la Plana (Spain) telf.: +34 964 244 178 www.cevica.es